



Xact H5701

 Series Servo



FEATURES

- For F3K DLG
- 6.5g weight & 6mm thick
- Speedy Response
- Incomparable Torque Performance
- High Precision with Zero Slop
- The Best Positioning Accuracy of Central Point
- Built-in Hall Sensor
- Programmable Travel Angle
- Robust CNC Aluminum Case with Metal Gear

SPECIFICATIONS

- Dimensions: 29.2*6*23mm (L*W*H)
- Weight: 6.5g
- Voltage range: 3.5-8.4V (6.0-8.4V is recommended)
- Telemetry: Current / Temperature / Travel Angle
- Frequency: 1520us / 333Hz, 760us
- Dead Band: 0.00fms
- Bearing Ball / Gear: Metal
- Motor Type: Coreless
- Servo Horn Spline: Ø4 15T
- Programmable: Yes, Travel Angle
- Port Type: FP2 (FBUS) / PWM / SBUS

| | @ 6.0V | @ 7.4V | @ 8.4V |
|----------------------|-----------|----------|-----------|
| Torque (kg*cm/oz*in) | 1.60/22.2 | 2.0/27.8 | 2.30/31.9 |
| Speed (S/60Deg) | 0.13 | 0.11 | 0.09 |


 FrSky Electronic Co., Ltd.
 Made in China